

SURGE PROTECTION DEVICE (SPD)



+91 95000 35752
enquiry@cikit.in
www.cikit.in

S.No	Product Code	SPD Configuration	Type	Max. operating voltage	Nominal discharge current (15 x 8/20 μ s impulses)	Max. discharge current (8/20 μ s impulses)	Protection mode
1	DS254VG - 300/G	3-phase+Neutral	Type 1+2+3	255 Vac	30 kA	70 kA	L/N and N/PE
2	DUT250VG-300/G	3-phase+Neutral	Type 1+2+3	255 Vac	40 kA	100 kA	L/N and N/PE
3	DS134R - 320/G	3-phase+Neutral	Type 1+2	320 Vac	20 kA	50 kA	L/N and N/PE
4	DAC50-31-320	3-phase+Neutral	Type 2	320 Vac	20 kA	50 kA	L/N and N/PE
5	DS102RS-230/G	Single phase	Type 1+2	320 Vac	30 kA	100 kA	L/N and N/PE
6	DAC50-11-320	Single phase	Type 2	320 Vac	20 kA	50 kA	L/N and N/PE
7	MLPC1-230L-R	Single phase	Type 2	320 Vac	5 kA	10 kA	L/N and N/PE
8	MJ8-CAT6S	CAT 6 cables	-	8 Vdc	"2 kA (x 10 - C2 Category)"	-	"Max. freq > 250 MHz Max. data rate = 10Gbps"
9	DLA-170	Telephone cables	-	170 Vdc	5 kA	20 kA	Max. freq > 10 MHz
10	BF PS 230V/20	For equipotential bonding	-		80 kA	150 kA	-
11	BP-LC	Load Cell Protector	-	40 Vac	-	20 kA	4 or 6 wires weighbridge system